

# Bolt 6 LT 1500 TX

## Video

### Video Inputs

3G-SDI SMPTE 424M standard / 75  $\Omega$  (BNC x 1)

1 x HDMI 1.4b Type-A receptacle

### Video Outputs

3G-SDI SMPTE 424M standard / 75  $\Omega$  (BNC x 1)

### Sdi Ancillary Data Support

Supports reading metadata, timecode, and start/stop flags from most camera manufacturers.

### Color Sampling

SDI: YCbCr 4:2:2, 10-bit/ HDMI: RGB/YCbCr 4:4:4 8-bit, 4:2:2 10-bit

### Delay Tx To Rx

<0.001sec

### Input Cross Conversion

Yes, HDMI to SDI (4Kp23.98-30 HDMI input is scaled and looped out as 1080p23.98-30 on SDI loopout)

## Supported Resolutions

### Supported Resolutions

4Kp23.98/24/25/29.97/30 (HDMI only)

1080p23.98/24/25/29.97/30/50/59.94/60

1080psf23.98/24/25/29.97/30

1080i50/59.94/60

720p50/59.94/60

480p59.94 576p50

480i(NTSC)/576i(PAL)

## Video Processing

### Video Compression

Visually Lossless

### Color Correction

None

## Audio Processing

### Audio Compression

48kHz 24-bit PCM

## Inputs

### Audio Input

Embedded SDI/HDMI Audio Input (2 Channel)

## Physical

### Dimensions

60mm x 103mm x 33mm

### Weight

206g (7.3oz)

### Construction

Milled Aluminum(Chassis) and regulation-compliant PCB

### Mountability

Multiple mounting options with 1/4"x20 and M3 holes

## Interfaces

### Configuration Interfaces

OSD with Menu, Joystick Navigation

### Switches

On/Off Switch

### Mobile App

Bolt App

### Desktop App

Bolt Manager application for OSX & Windows

### Usb Interface Functionality

Upgrade via Micro-USB

### Bluetooth

2.4 GHz

## Network

### Antennas

2 External 2dBi antennas (included)

### Wireless

Non-DFS Frequencies:

5.190 ~ 5.230 GHz, 5.755 ~ 5.795 GHz, 5.945 ~ 6.425GHz

DFS Frequencies:

5.270 ~ 5.670 GHz

### **Rf Channel Selection**

Auto, Manual

### **Encryption**

AES-256, RSA-1024 key exchange

### **Rf Power**

23 dbm EIRP

### **Range**

Up to 1500 ft, line of sight

### **Unicast Multicast**

Can connect one Transmitter to up to 6 Receivers

### **Noise Rejection**

Can coexist with WiFi and 5GHz cordless phones

Can operate up to 6 sets in same location

### **Interoperability**

Can transmit wireless video to all ranges of Bolt 4K XT and Bolt 4K LT receivers (limited by shortest range device)

## **Power**

### **Power Input**

2-Pin Circular locking Connector 6-28 VDC

### **Battery**

None, optional Sony/Canon dual battery plate

### **Nominal Power Consumption**

9 Watts

## **Environmental**

### **Operating Temperature**

0-40°C