

ePTZ Tracking Camera

Connectors

Video Output: 1 x HDMI, 1x USB 3.0

Audio: 1 x 3.5mm input Audio Jack

Communication: RS232 1x3 pin connector, RS485 1x2 pin connector, LAN (Support PoE) 1 x RJ45

Camera

Sensor: 1/2.8" high-quality 4K CMOS sensor

Focus Lens: f=6.8mm

View Angle: 51.6° (D), 45.5° (H), 26.5° (V)

Digital Zoom: 3x

Minimum Illumination: 0.1Lux (F1.8, AGC ON)

DNR: 2D & 3D DNR

White Balance: Auto/Manual/One key/Specific Color Temp. (2400K~7100K, step size 100)

Focus: Fixed

Exposure: Auto/Manual/Shutter Priority/Brightness Priority

BLC: On/Off

SNR: >50dB

Effective Pixels: 828m, 16:9

Video Output Resolution

HDMI: 1080p30/29.97/25 | 720p/29.97

USB 3.0: 1080p30/29.97/25 | 720/29.97

Audio Compression Format: AAC / MP3 / G.711A

Video Compression Format: H.264 / H.265 / YUY2 / NV12

Baude Rate (bds): 115200 / 9600 / 4800 / 2400bps

Network Protocol: RTSP / RTMP / SRT / ONVIF / GB/T28181 / VISCA

Communication Protocol: VISCA, Pelco-D, Pelco-P

Power

Input Voltage: DC12V

Max Poser: 5W

Working Environment

Temperature: -10°C~50°C

Humidity: 20%~80%

Physical

Weight: 0.53 kg

Dimensions: 148 x 76 x 76 mm