

# TP2R/TP4R/TP8R Technical data

Model	TP2R	TP4R	TP8R
DC Inputs	20V=1.3A	20V=2.35A	20V=4.15A
Input Power	≈26W	≈47W	≈83W
Lithium Battery	14.4V 3000mAh	14.4V 6000mAh	14.4V 12000mAh
Power Supplies	DC Power Supply/Lithium Battery Power Supply /V-mount Battery Power Supply		
Note: The V-mount battery should be 14.8V or 26V 100Wh above and sold separately.			
Battery Life (in 100% brightness)	Approx. 120min	Approx. 150min	Approx. 180min
Charging Time	Approx. 120min	Approx. 150min	Approx. 180min
Waterproof Grade		IP65	
Average TLCI		≥96	
Average CRI		≥96	
CCT Range		2000K-10000K	
Mode	5 modes: CCT mode, HSI mode, RGB mode, GEL mode, FX mode		
FX Types	17		
Controlling Methods	DMX512 control, Bluetooth APP control, CRMX control, Light body control, RDM control		
Bluetooth Controlling Distance		Max. 30m	
Wireless Controlling Distance	Max. 150m		Max. 100m
Working Environment Temperature	-10°C~40°C		
Dimension	47mm*47mm*600mm	47mm*47mm*1200mm	47mm*47mm*2300mm
Net weight≈	0.84kg	1.5kg	2.94kg