

RGB10X-USB-BK

Connectors

Video: USB 2.0 (1xUSB-A)

Communication: RS232 (2xDIN 8), RS485 (1x2 Pin Terminal Connector)

Power: 1xHEC3800 DC Socket

Camera

Optical Zoom: 10x f=4,34~41.66mm

View Angle: 8.8° ~ 70°

AV: F1.85 ~ F2.43

Digital Zoom: 10x

Minimum Illumination: 0.5 lux (F1.8, AGC ON)

DNR: 2D & 3D DNR

White Balance: Auto/Manual/One Push/3000K - 7000K

Focus: Auto/Manual/OnePush

Exposure: Auto/Manual

BLC: On/Off

Video Adjustment: Brightness/Color/Saturation/Contrast/Sharpness/B | W mode/ Gamma curve

SNR: >55db

Effective Pixels: 2.07m, 16:9

Pan- and Tilt-Parameter

Movement: -170° ~ +170° / '-30° ~ +90°

Control Speed: 0.1 ~ 60°/s, 0.1 ~ 30°/s

Preset Speed/Quantity: Pan: 60°/s, Tilt: 30°/s, Up to 255 preset positions (10 remote control)

Video Compression: Format MJPG | H.264 | H.265

Output Resolutions: 720p@25/30 | 1080p@25/30

Control Protocol: VISCA | Pelco-D | Pelco-P

Operating System: Windows 7 | Windows8 | Windows10 | Mac osx | Linux

USB Communication: Protocol UVC

Power

Input Voltage: DC12V/0.25A

Max Power: 2.5W

Environment

Temperature: -10°C~50°C

Humidity: 20%~80%

Physical

Weight: 1kg

Dimension: 156.8mm×112.6mm×139.5mm